



SPECIFICATIONS
 CURRENT RATING: 2 AMP MAX.
 INSULATION RESISTANCE: 1000M OHMS MIN.
 DIELECTRIC WITHSTANDING: 1000V AC/DC
 CONTACT RESISTANCE: 30m OHMS MAX.
 OPERATING TEMPERATURE: -25°C ~ +85°C
 MATERIALS
 CONTACT MATERIAL: PHOSPHOR BRONZE
 INSULATION MATERIAL: NYLON 9T UL 94V-0

CPQL 120 935 P VB-FG

Contact No. _____

H=9.35mm

Press Fit

FG=ROHS Compliant

Contact plating

Definition	Code
Gold flash	VB
10u"	VE
15u"	VF
30u"	VJ

APTOS TECHNOLOGY CONFIDENTIAL
 This document, and all information it contains, are the confidential, proprietary property of APTOS Technology. Disclosure, duplication or distribution of this document, or any information it contains, in whole or part, without prior written permission from APTOS Technology is strictly prohibited.

GENERAL TOLERANCE UNLESS OTHERWISE SPECIFIED			
XXX	± X	.XX	± 0.10
XX	± X	.XXX	± X
X	± 0.50	X.	± 1"
.X	± 0.30	.X	± X

REV.	A	DATE	DESCRIPTION

SCALE	UNIT
	mm

APPROVED	DATE

FILE NAME:
CPQL-120 LP APDLING

APTOS TECHNOLOGY

CPQL Series

PC104 Plus Press-Fit Stacking

PRODUCT NO. CPQL120935PVB-FG

