






N=Number of contacts



SPECIFICATIONS

Voltage Rating: 300VAC/300VAC
 Current Rating: 20 Amps/20 Amps
 Dielectric withstanding: 1.6KV/2.5KV
 Operating Temperature: -40°C to +115°C
 Contact Material: PhBz, Tin Plated
 Terminal Screw: Steel Zinc plating "-" slot type
 Insulator Material: Thermoplastic, UL 94V-0
 Wire Range: 0.34-2.5mm²
 Wire Strip Length: 6-7mm
 Solid/Stranded Wire: 12-22 AWG
 Torque: 3.5Lb-In/0.4Nm
 Clamp: Steel Zinc plated
 Screw: M2.5
 Safety Approval: us TÜV

RPEN-XXGEXJ-FG

NO. OF POLES
 2 POLES
 3 POLES
 ...
 24 POLES

FG: RoHS Compliant
 Pb<40000ppm

Color

J: Black(RAL9005)
 B: Red(RAL3001/D)
 C: Orange(RAL2011/P)
 D: Yellow(RAL1018/A)
 E: Green(RAL6018/T)
 F: Blue(RAL5015/A)
 H: Grey(RAL7035/D)

APTOS Technology CONFIDENTIAL
 This document, and all information it contains, are the confidential, proprietary property of APTOS Technology. Disclosure, duplication or distribution of this document, or any information it contains, in whole or part, without prior written permission from APTOS Technology is strictly prohibited

Poles		02	03	04	05	06	07	08	09	10	11	12
Dim A		10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00
Dim B		5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00
Tolerance	±0.20						±0.25					
Poles	13	14	15	16	17	18	19	20	21	22	23	24
Dim A	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.0	110.00	115.00	120.00
Dim B	60.00	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.00	110.00	115.00
Tolerance	±0.30						±0.40					

GENERAL TOLERANCE UNLESS OTHERWISE SPECIFIED			
XXX.	±	X	.XX ± 0.10
XX.	±	X	.XXX ± X
X.	±	0.50	X." ± 1"
.X	±	0.30	.X" ± 1"
REV.	A	DRAWN	09/02/09
DATE	09/02/09	CHECKED	
SCALE	As shown	APPROVED	
UNIT	mm		SIZE A4

AP APTOS TECHNOLOGY

RPEN Series
 5.0 mm Plug

PRODUCT NO. RPEN-XXGEXJ-FG

FILE NAME: RPEN-XXGEXJ-FG LF APD.DWG