





SPECIFICATIONS

- Voltage Rating: 300VAC
- Current Rating: 20 Amps
- Dielectric withstanding: 1.6KV
- Operating Temperature: -40°C to +115°C
- Contact Material: PhBz(CuSn), Tin Plated
- Terminal Screw: Steel Zinc plating "-" slot type
- Insulator Material: Thermoplastic, UL 94V-0
- Wire Range:
- Wire Strip Length: 8-9mm
- Solid/Stranded Wire: 12-22 AWG
- Torque: 3.5Lb-In
- Clamp: Steel Zinc plated
- Screw: M2.5
- Safety Approval: 



RPEN-XXJEXA-FG


- NO. OF POLES
 - 2 POLES
 - 3 POLES
 - ...
 - 16 POLES
- Color
 - J: Black(RAL9005)
 - B: Red(RAL3001/D)
 - C: Orange(RAL2011/P)
 - D: Yellow(RAL1018/A)
 - E: Green(RAL6018/T)
 - F: Blue(RAL5015/A)
 - H: Grey(RAL7035/D)
- FG: RoHS Compliant
Pb<40000ppm

APTOS Technology CONFIDENTIAL
 This document, and all information it contains, are the confidential, proprietary property of APTOS Technology. Disclosure, duplication or distribution of this document, or any information it contains, in whole or part, without prior written permission from APTOS Technology is strictly prohibited

Poles		02	03	04	05	06	07	08	
Dim A		13.24	20.86	28.48	36.10	43.72	51.34	58.96	
Dim B		7.62	15.24	22.86	30.48	38.10	45.72	53.34	
Tolerance		±0.15			±0.20				
Poles		09	10	11	12	13	14	15	16
Dim A		66.58	74.20	71.82	89.44	97.06	104.68	112.30	119.92
Dim B		60.96	68.58	76.20	83.82	91.44	99.06	106.68	114.30
Tolerance		±0.30			±0.40				

GENERAL TOLERANCE UNLESS OTHERWISE SPECIFIED	
XXX. ± X	.XX ± 0.10
XX. ± X	.XXX ± X
X. ± 0.50	X.' ± 1'
.X ± 0.30	.X' ± 1'



REV. A	DRAWN	09/29/08	RPEN Series 7.62 mm Plug
DATE 09/29/08	CHECKED		
SCALE As shown	APPROVED		PRODUCT NO. RPEN-XXJEXA-FG
UNIT mm		SIZE A4	FILE NAME RPEN-XXJEXA-FG LF APD.DWG