



SPECIFICATIONS

- Current Rating: 1 Amps
- Insulator Resistance: 5000 Megaohms min.
- Contact Resistance: 20 m ohms max.
- Dielectric withstanding: AC 500V
- Operating Temperature: -40°C~+105°C
- Contact Material: Phosphor Bronze
- Insulator Material: Polyester, UL 94V-0
- © Standard: Nylon-6T
- Finish: Gold Plated
- © Standard: Gold Flash all over

SPUBF-XX-XX-X-X-FG

Number of Contacts: []

Contact Plating: []

High temp RoHS Compliant (Nylon-6T or Greater)

E: Metal Pad & Tube
B: Metal Pad & Reel

0:W/O Locating peg
1:With Locating peg

Definition	Code
© Gold plated:	
flash VB	10µ" VE
3µ" VC	15µ" VF
5µ" VD	30µ" VJ

APTOS Technology CONFIDENTIAL

This document, and all information it contains, are the confidential, proprietary property of APTOS Technology. Disclosure, duplication or distribution of this document, or any information it contains, in whole or part, without prior written permission from APTOS Technology is strictly prohibited

GENERAL TOLERANCE UNLESS OTHERWISE SPECIFIED			
XXX. ± X	.XX ± 0.25	<div style="text-align: center;"> </div>	
XX. ± X	.XXX ± X		
X. ± X	X' ± 3'		
.X ± 0.38	.X' ± X'		
REV. A	DRAWN	07/18/08	SPUBF Series
DATE 07/18/08	CHECKED		1.00mm SMT Socket - Dual Entry
SCALE As Shown	APPROVED		PRODUCT NO. SPUBF-XX-XX-X-X-FG
UNIT mm		SIZE A4	FILE NAME: SPUBF LF APD.DWG