


Mounting Hole



SPECIFICATION

MATERIAL

Insulator: Thermosetting Polymer

Contacts: Brass

Contacts plating

Underplate: 50u" Min Nickel

Contact area: 1u" Gold

General Data

Operating Voltage: 30V AC

Current rating: 3 Amps max.

Contact resistance: 0.5 ohms Max

Insulation resistance: 100 Mohms min @ 500 VDC

Degree of protection: IP 67

Temperature range: -25°C TO +85°C

Part no.

W8FB XX F S S E2 N B D 3 FG
1 2 3 4 5 6 7 8 9 10 11

1.SERIES NO.

W8FB=M8 series

2.CONTACT NUMBER:

05=5PINS

3.CONTACT TYPE:

F=FEMALE

4.CONTACT AREA PLATING:

S=1u" GOLD

5.SOLDER TAILS AREA PLATING:

S=1u" GOLD

6.APPLY TYPE:

E2=M8 Through Panel

7.SHELL PLATING:

N=Ni

8.CODING:

B=B Coding

9.PACKING STYLE:

D=BAG

10.INSULATOR COLOR:

3=Black

11.GREEN OPTION:

FG=RoHS



For SIP

For cmk/cpk

APTOS Technology CONFIDENTIAL
This document, and all information it contains, are the confidential, proprietary property of APTOS Technology. Disclosure, duplication or distribution of this document, or any information it contains, in whole or part, without prior written permission from APTOS Technology is strictly prohibited

ANG. 0. ±2° .0 ±0.30 .00 ±0.20 .00 ±0.10		UNIT: mm			
SCALE: AS SHOWN					
DRAWN JG		01/04/2018		DRAWING NAME: M8 B-Code 5 Pin Female Conn.	
CHECKED		/ /		PRODUCT NO. W8FB-05FSSE2NBD3	
APPROVED		/ /		FILE NAME: W8FB-05FSSE2NBD3.dwg	
REV.		SIZE A4	REV. B		

REV.	DESCRIPTION	DATE
1		
2		
3		
4		
5		
6		